

OPERATION MANUAL



NOTE: Tasmota is not a commercial product and

support is limited. You must be willing to independently investigate and resolve potential issues.

Detailed information about connection, changing settings and modifications is presented on the website " <https://tasmota.github.io/docs/> "

description

The NOUS L6t smart Wi-Fi switch with Tasmota open software installed (hereinafter referred to as the smart switch) is designed to organize automatic and manual shutdown of devices in the room, through remote access via a Wi-Fi network, using a smartphone or from a personal PC via the Web interface. Communication with the smart switch is configured via a Wi-Fi network, for which a wireless Wi-Fi adapter is used. It is equipped with a mechanical button and a global indication of the device's status. It is also equipped with an electromechanical relay.



ATTENTION: The connection of the smart switch to the Wi-Fi network

cannot be guaranteed in all cases, as it depends on many conditions: the quality of the communication channel and intermediate network equipment, the brand and model of the mobile device, the version of the operating system, etc.


PRECAUTIONS

- Read this manual carefully.
- Use the product within the temperature and humidity limits specified in the technical data sheet.
- Do not install the product near heat sources such as radiators, etc.
- Do not allow the device to fall and be subject to mechanical loads.
- Do not use chemically active and abrasive detergents to clean the product. Use a damp flannel cloth for this.
- Do not overload the specified capacity. This may cause short circuit and electric shock.
- Do not disassemble the product yourself - diagnostics and repair of the device must

be carried out only in a certified service center.

- Please contact the seller for a replacement if there is damage caused by shipping.

Design and controls





No.	Name	description
1	Indicator/Button	Shows the current status of the device / A short press of the button switches USB "ON" "OFF".
2	Network indicator	Indicates the status of the network connection

installation

The smart switch is mounted in a regular socket

Installation procedure:


1	Remove protective covers	
2	Connect the smart switch as shown in the electrical diagram.	
3	Install the smart switch in the socket, then install the external panel.	
4	When the installation is complete, the device is ready to use.	
	Importantly:	Make sure that the Wi-Fi network is stable and has a sufficient level in the chosen installation location.

Connection

A smartphone or PC is required to connect the Nous L6T smart switch.

The procedure for connecting the smart switch to the Wi-Fi network:

1	Make sure that the frequency range of the network to which the device will be connected is 2.4 GHz, otherwise the smart switch will not connect, since it is not designed to work with 5 GHz Wi-Fi networks;
---	--

10	{"NAME":" NOUS Smart breaker L6T", "GPIO":[1,1,1,1,32,224,1,1,1,544,224,1,1,1], "FLAG":0, "BASE":18} The template must be entered in the "Template" field, check the "Activate" box and save the changes:  If you have a product older than 09.2023, then the template will be as follows <pre>{\"NAME\":\" NOUS Smart breaker L6T\", \"GPIO\":[1,1,1,1,2720,224,1,1,544,2624,32,2656,0,0], \"FLAG\":0, \"BASE\":18}</pre>
eleven	To reset the smart switch to factory settings, you need: Plug and unplug the device 6 times and leave it on for the 7th - the LED should start flashing, this means the smart switch is ready to be connected again; if there is access to the web interface, then type " reset 1" in the console and press "enter"
Tasmota is a highly extensible and flexible application that can be integrated with: Alexa, AWS IoT, Domoticz, Home Assistant, Homebridge, HomeSeer, IP Symcon, KNX, NodeRed, nymea, OctoPrint, openHAB, Otto, IOBroker, Mozilla WebThings Adapter, SmartThings, Tasmohab, Homematic ip touch. for more information see here: https://tasmota.github.io/docs/Integrations/	